# **SAFCO (Services) Ltd**

Executive Suite 4, First Floor, Gamma 1 West Road, Ipswich, Suffolk IP3 9FF



# **Container Specification**

The information below is for reference only

IP3 9FF
Tel no +44(0)1473 313041
Email info@safcoservices.com

#### DRY CARGO CONTAINERS

	Container weight				Interior	Door Open			
Type	Gross (kg)	Tare (kg)	Net (kg)	Length (m)	Width (m)	Height (m)	Capacity (m3)	Width (m)	Height (m)
20 ft	24,000	2,370	21,630	5.898	2.352	2.394	33.20	2.343	2.28
40 ft	30,480	4,000	26,480	12.031	2.352	2.394	67.74	2.343	2.28

Manufactured from either aluminium or steel, they are suitable for most types of cargo / general cargo. Aluminium containers have a slightly larger payload than steel, and steel cotainers have slightly larger internal capacity

#### HIGH CUBE CONTAINERS

	Container weight				Interior I	Door Open			
Type	Gross (kg)	Tare (kg)	Net (kg)	Length (m)	Width (kg)	Height (kg)	Capacity (m3)	Width (m)	Height (m)
40 ft	30,480	3,980	26,500	12.031	2.352	2.698	76.30	2.340	2.585
45 ft	30,480	4,800	25,680	13.544	2.352	2.698	86.00	2.340	2.585

With high cube containers you can gain extra height compared to general purpose containers. Ideal for light, voluminous cargo or bulky cargo. These extra volume containers come in aluminium and steel

#### REFRIGERATED CONTAINERS

	Container weight				Interior	Door Open			
Туре	Gross (kg)	Tare (kg)	Net (kg)	Length (m)	Width (kg)	Height (kg)	Capacity (m3)	Width (m)	Height (m)
20 ft	24,000	3,050	20,950	5.449	- 2.290	2.244	26.70	2.276	2.261
40 ft	30,480	4,520	25,960	11.690	2.250	2.247	57.10	2.280	2.205

Recommended for delicate cargo, Bottom-air delivery system ensures refrigerated cargo reaches its destination in optimum condition.

## **OPEN TOP CONTAINERS**

	Container weight				Interior I	Door Open			
Type	Gross (kg)	Tare (kg)	Net (kg)	Length (m)	Width (kg)	Height (kg)	Capacity (m3)	Width (m)	Height (m)
20 ft	24,000	2,580	21,420	5.629	2.212	2.311	32.00	2.330	2.263
40 ft	30,480	4,290	26,190	11.763	2.212	2.311	65.40	2.330	2.263

Allowing cargo to be loaded from the top, open top containers are particularly suitable for bully cargo such as machinery. They are fitted with PVC tarpulin cover and attachable bows with cable devices. The container doors can be removed to make the stuffing of cargo more convenient. Manufactured of Steel

### **GARMENT CONTAINERS**

	Container weight				Interior	Door Open			
Type	Gross (kg)	Tare (kg)	Net (kg)	Length (m)	Width (kg)	Height (kg)	Capacity (m3)	Width (m)	Height (m)
20ft	24,000	2,240	21.760	5.898	2.352	2.394	33.20	2.343	2.280
40ft	30,480	3,885	26.595	12.031	2.352	2.394	67.74	2.343	2.280

Used for all kinds of garments. The containers are specially designed for garment product and related industry. There are some options of using a string or bar system, or a combination of both. The containers allow increased flexibility, greater load internal capacity and savings on transport and handling costs.

#### **FLAT RACK CONTAINERS**

	Con	tainer weig	ht	Interior Measurement					
Type	Gross (kg)	Tare (kg)	Net (kg)	Length (m)	Width (kg)	Height (kg)	Capacity (m3)		
20 ft	30,480	2,900	27,580	5.624	2.236	2.234	27.90		
40 ft	34,000	5,870	28,130	11.786	2.236	1.968	51.90		

Flat Racks are especially suited to heavy loads or cargo that needs loading from the top and sides such as piopes or macjinery. There are collapsible and non-collapsible containers with or without walls. Manufactured of Steel.